

DIGI Water in Oil Test Kit

디지털 수분 측정기

Lubrication Plus®
QUMENSUS



Lubrication Plus
SOLGE

(주)솔지 | 대구광역시 달성군 다사읍 세천북로8길 11 T. 053-588-3301 E. cs@solge.com www.solge.com

DIGI Water Test Kit

디지털 수분 측정기

■ 개요

DIGI Water Test Kit 수분 측정기는 디지털 방식으로 저가형 수분측정기 임에도 불구하고 정확도가 고가의 수분 측정장비와 비교하여도 전혀 손색이 없으며 현장용으로 사용법이 매우 간편합니다.

유압유, 윤활유 외 매우 다양한 유체속에 함유된 수분 분석이 가능하며 가능한 유체는 내부 부식과 찌꺼기와 적합성에만 문제가 없다면 어떤 유체 분석도 가능합니다.

■ 수분이 기계에 미치는 영향

1. 부식 유발
2. 유막 강도 약화
3. 공동현상 유발
4. 침적과 필터 눈막힘 현상 초래

■ 수분이 기유 미치는 영향

1. 가수분해와 산화촉진
2. Aeration
3. 점도변화
4. 오일의 절연성 파괴

■ 특징

1. DIGI Water in Oil Test Kit

- 측정범위 : 0.02-1%, 200-10,000 ppm, 0-10%, 0-20%
- 정확도 : $\pm 0.1\%$ on 0-10% range
- 측정시간 : 2 분
- 측정시약 : non hazardous

2. DIGI Water in Oil Test Kit (Low Range)

- 측정범위 : 0.02-1%, 100-3,000 ppm, 0-10%
- 정확도 : $\pm 0.1\%$ on 0-10% range
- 측정시간 : 5 분
- 측정시약 : non hazardous



DIGI Cell

DIGI Water Test Kit

디지털 수분 측정기

측정방법



주문 Part Number

No	품명	품번	규격	단위	수량
1	DIGI Water in Oil Test Kit	SK1W	0.02-1%, 200-10,000 ppm, 0-10%, 0-20%	Set	1
2	DIGI Water in Oil Test Kit (Low Range)	SK1W-L	0.02-1%, 100-3,000 ppm, 0-10%	Set	1

소모품

No	품명	품번	구성품	단위	수량
1	Water in Oil Reagent Pack (50회)	FG-K2-101-KW	Reagent A (500mLx2) Paste Reagent (50ea)	Set	1
2	Water in Oil Reagent Pack (50회) Low Range	FG-K19581-KW	Reagent A (500mLx3) Paste Reagent (50ea)	Set	1